
High Performance Carbide Tap and HSS Tap Series

TAP series

KORLOY
TECH-NEWS



- Excellent Wear Resistance. Highly durable carbide tap and HSS Tap series.
- A variety of taps including point taps, spiral taps, straight taps, roll taps, and more to meet a wide range of requirements, available for JIS and DIN standards in metric threads.

High Performance Carbide Tap and HSS Tap Series

TAP series

KORLOY developed **carbide taps** and HSS taps that meet the demand for productivity. Carbide taps now have increased wear resistance and extended tool life by the use of high toughness substrate. There are TiN / TiCN coated and non-coated products for a wide range of applications.

HSS taps have a high vanadium body to provide excellent cutting performance. Its wide lineup of coated and non-coated taps, and the HOMO series is available for various workpieces.

KORLOY taps were standardized not only to JIS but to DIN in metric threads. It is possible to machine a com-

prehensive range of workpieces with KORLOY point taps, spiral taps, straight taps, roll taps and more. A straight tap is used for through holes, mass production, cast iron, medium carbon steel, and non ferrous metal. A point tap has a similar shape to a straight tap but provides smoother chip evacuation for through holes. A spiral tap is optimized for blind hole making by evacuating chips through flutes. A roll tap is for making both through holes and blind holes on non ferrous metals such as aluminum.

KORLOY taps ensure maximum cutting efficiency with its excellent price competitiveness, quality, and a wide selection of products.



Carbide Taps

- High toughness substrate

HSS

- High vanadium substrate

Applicable to various workpiece forms

- A wide selection composed of point taps, spiral taps, straight taps, roll taps and more

Broad line-ups per type and size

- A wide choice with various types and sizes

Code System

Thread Appearance

ST: Straight Tap
 PT: Point Tap
 SP: Spiral Tap
 RT: Roll Tap
 SR: Spiral roll Tap
 STD: Straight Tap (DIN)
 PTD: Point Tap (DIN)
 SPD: Spiral Tap (DIN)
 RTD: Roll Tap (DIN)

M3 x 0.5	-	ST	25	(S)	-	(120)
Metric coarse screw threads and thread size	Appearance	Incomplete thread length	Roll Tap	Overall length	S: Single M: Multi	Special type

Grade System

Carbide Tap		HSS Tap	
FN30T	Carbide, Uncoated	HN30T	HSS, Uncoated
PC20T	Carbide, TiN coating	HC20T	HSS, TiN coating
PC10T	Carbide, TiCN coating	HC10T	HSS, TiCN coating
-		HH30T	HSS, HOMO Treatment

Carbide Tap Series

Carbide taps have excellent tool life and wear resistance due to high toughness substrate.

Tap type	Figure	Feature	Grade	Size
ST Straight Tap		For through holes and mass production For cast iron, medium carbon steel and non ferrous metal	FN30T	M3-M12
			PC10T	M3-M12
			PC20T	M3-M12
SP Spiral Tap		For blind holes Chip evacuation through flutes	FN30T	M3-M12
			PC10T	M3-M12
RT Roll Tap		For non ferrous metal For through holes and blind holes	FN30T	M3-M12
			PC10T	M3-M12
SR Spiral Roll Tap		For non ferrous metal, Al and magnesium	FN30T	M3-M6
			PC10T	M3-M6

HSS Tap Series

HSS taps show improved performance due to high vanadium substrate.


Tap type		Figure	Feature	Grade	Size
ST	Straight Tap		For through holes and mass production For cast iron, medium carbon steel and non ferrous metal	HN30T	M3-M20
				HC20T	M3-M20
				HC10T	M3-M20
				HH30T	M8-M16
PT	Point Tap		For through holes and mass production Similar shape to the straight type but specialized with easier chip evacuation	HN030T	M3-M20
				HC20T	M3-M20
				HC10T	M3-M20
				HH30T	M3-M20
SP	Spiral Tap		For blind holes Chip evacuation through flutes	HN30T	M3-M20
				HC20T	M3-M20
				HC10T	M3-M20
				HH30T	M3-M24
RT	Roll Tap		For non ferrous metal For through holes and blind holes	HN30T	M3-M12
				HC20T	M3-M12
				HC10T	M3-M12
SR	Spiral Roll Tap		For non ferrous metal, Al and magnesium	HN30T	M3-M6
				HC20T	M3-M6
				HC10T	M3-M6




KH Stepped Accuracy System

The KH stepped accuracy system was applied to KORLOY taps to obtain the required precision of nuts.
→ Possible to select proper tools for cutting conditions

Comparison of Effective Diameters of a Thread - M3x0.5



Comparison of Effective Diameters of a Thread - M10x1.5



* $\{P \leq 0.6 \text{ (T.P.I} \geq 40\}\}$

Upper tolerance: $0.010 + 0.015 \times n$

Under tolerance: Upper tolerance - 0.015 (mm)

* $\{P \geq 0.7 \text{ (T.P.I} \leq 36\}\}$


Upper tolerance: $0.020 \times n$

Under tolerance: Upper tolerance - 0.020 (mm)


GH Stepped Accuracy System

Taps without a flute such as roll taps require strict bottom hole managing due to plastic deformation in nut machining. KORLOY uses a stepped accuracy system of tolerance within $12.7\mu\text{m}$ (0.0005).

Comparison of Effective Diameters of a Thread - M3x0.5



Comparison of Effective Diameters of a Thread - M10x1.5



Recommended Cutting Speeds and Cutting Fluid

- For machining cold / hot forging steel and sintered ferrous alloy in high feed, high depth of cut and highly interrupted conditions
- Excellent resistance to chipping, fracture and thermal crack
- Improved surface finish due to optimized cutting edges

ISO	Workpiece		Cutting speed, vc(m/min)					Cutting fluid			
			Straight Tap	Spiral Tap	Point Tap	Carbide Tap	Roll Tap	Insoluble	Water soluble emulsion	Semi dry	Dry
P	Low carbon steel	≥ 0.25 %C	8~13	8~13	15~25	-	8~13	◎	○	△	△
	Medium carbon steel	≥ 0.25~0.45 %C	7~12	7~12	10~15	-	7~10	◎	○	△	△
	High carbon steel	≥ 0.45 %C	6~9	6~9	8~13	-	5~8	◎	○	△	△
	Alloy steel	SCM	7~12	7~12	10~15	-	5~8	◎	△	△	△
	Quenched and tempered steel	25~45HRC	3~5	3~5	4~6	-	-	◎	△	-	-
	Tool steel	SKD	6~9	6~9	7~10	-	-	◎	-	-	-
	Cast steel	SCM	6~11	6~11	10~15	-	-	◎	○	-	-
M	Stainless steel	SUS	4~7	5~8	8~13	-	5~10	◎	○	-	-
	Precipitation hardened stainless steel	SUS630 SUS631	3~5	3~5	4~6	-	-	◎	-	-	-
K	Cast iron	FC	10~15	-	-	10~20	-	◎	○	○	○
	Ductile cast iron	FCD	7~12	7~12	10~20	10~20	-	◎	○	○	-
N	Copper	Cu	6~9	6~11	7~12	10~20	7~12	○	○	-	-
	Brass, brass-cast	Bs Bsc	10~15	10~20	15~25	15~25	7~12	○	○	○	○
	Bronze, bronze-cast	PB PBC	6~11	6~11	10~20	10~20	7~12	○	○	-	-
	Rolled aluminum	Al	10~20	10~20	15~25	-	10~20	◎	○	△	-
	Aluminum-cast, alloyed	AC ACD	10~15	10~15	15~20	10~20	10~25	◎	○	△	-
	Magnesium-cast, alloyed	MC	7~12	7~12	10~15	10~20	-	◎	○	○	-
	Zinc-cast, alloyed	ZDC	1~12	7~12	10~15	10~20	7~12	◎	○	△	-
	Thermosetting plastics	Bakelite phenol epoxy	10~20	-	-	15~25	-	-	○	○	○
	Thermoplastics	Nylon vinyl chloride	10~20	10~15	10~20	10~20	-	-	○	○	○

◎ Recommended ○ Applicable △ Usable - Unusable

Recommended Drill Diameter [on 2nd class thread basis]

Straight Tap & Spiral Tap

Refer to this table for information about drill diameters per thread size of straight taps and spiral taps.

Thread size	Drill diameter		
	Min	Recommended	Max
M3X0.5	2.459	2.5	2.599
M4X0.7	3.242	3.3	3.422
M5X0.8	4.134	4.2	4.334
M6X1.0	4.917	5.0	5.153
M8X1.25	6.647	6.8	6.912
M10X1.25	8.647	8.8	8.912
M10X1.5	8.376	8.5	8.676
M12X1.0	10.917	11.0	11.153
M12X1.25	10.647	10.8	10.912
M12X1.5	10.376	10.5	10.676


Thread size	Drill diameter		
	Min	Recommended	Max
M12X1.75	10.106	10.3	10.441
M14X1.5	12.376	12.5	12.676
M14X2.0	11.835	12.0	12.21
M16X1.5	14.376	14.5	14.676
M16X2.0	13.835	14.0	14.21
M18X1.5	16.376	16.5	16.676
M18X2.5	15.294	15.5	15.744
M20X1.5	18.376	18.5	18.676
M20X2.5	17.294	17.5	17.744
-	-	-	-

Roll Tap

Refer to this table for information about drill diameters per thread size of roll taps.

Thread size	Drill diameter		
	Min	Recommended	Max
M3X0.5	2.76	2.8	2.81
M4X0.7	3.65	3.7	3.7
M5X0.8	4.59	4.6	4.66
M6X1.0	5.48	5.5	5.57
M8X1.25	7.34	7.4	7.41
M10X1.25	9.34	9.4	9.41

Thread size	Drill diameter		
	Min	Recommended	Max
M10X1.5	9.18	9.2	9.28
M12X1.0	11.48	11.5	11.57
M12X1.25	11.34	11.4	11.41
M12X1.5	11.18	11.2	11.28
M12X1.75	11.05	11.1	11.15
-	-	-	-



- Pre-hole diameter = D1 : Major diameter
D2 : Minor diameter
- $a = \frac{1}{2} \times (D_1 - D_2)$
- $h = \text{Height of fundamental triangle}$
- Rate of threading engagement = $a/h \times 100\%$

$$\text{*Rate of threading engagement} = \frac{\text{Major diameter} - \text{Pre-hole diameter}}{2 \times (\text{Height of fundamental triangle})}$$

$$\text{* Pre-hole diameter} = d - 2 \times H \times \frac{\text{rate of threading engagement}}{100}$$

- d : Major diameter
- H (Rate of threading engagement's Height)
: 0.541266P
- P : Pitch(mm)

* Recommended bottom hole diameters follow the JIS standard for a nut. (Nuts outside the JIS standard are excluded.)

$$\text{* Drill diameter} = D - 0.0068 \times P \times 65$$

- D : Nominal diameter
- P : Pitch(mm)
- 65 = 65% of the thread height

* Nut's bottom hole diameters outside the JIS standard are only for reference.

Application Examples



Cutting tool

- Workpiece SNCM439 (HRC43)
- Cutting conditions Drill diameter(\emptyset) = 4, vf(mm/min) = 70, ap(mm) = 13, wet
- Tool M4x0.7-PT25 (HC20T)

Korloy

143ea/edge

Competitor A

110ea/edge

30% more

➔ 30% longer tool life than competitor A



Plate

- Workpiece SNCM439 (HRC40)
- Cutting conditions Drill diameter(\emptyset) = 5, vf(mm/min) = 80, ap(mm) = 15, wet
- Tool M5x0.8-PT25 (HC20T)

Korloy

210ea/edge

Competitor B

140ea/edge

50% more

➔ 50% longer tool life than competitor B



Break part (Caliper)

- Workpiece FCD50
- Cutting conditions Drill diameter(\emptyset) = 6, vf(mm/min) = 100, ap(mm) = 10, wet
- Tool M6x1.0-PT25 (HC20T)

Korloy

90ea/edge

Competitor C

70ea/edge

28% more

➔ 28% longer tool life than competitor C



Cutting tool (Side cutter)

- Workpiece SNCM439
- Cutting conditions Drill diameter(\emptyset) = 5, vf(mm/min) = 80, ap(mm) = 8, wet
- Tool M5x0.8-SP (HC20T)

Korloy

180ea/edge

Competitor D


150ea/edge

20% more

➔ 20% longer tool life than competitor D

Carbide Tap

ST type (Straight Tap)



(mm)

Flutes	Designation		Thread size	L (Overall length)	I (Thread length)	d (Shank diameter)	K (Square width)	Kl (Square length)	Limits	
	1.5P	3P								
3	M3X0.5-ST15	M3X0.5-ST30	M3X0.5	46	11	4.0	3.2	6	KH3	
	M4X0.7-ST15	M4X0.7-ST30	M4X0.7	52	13	5.0	4.0	7		
	M5X0.8-ST15	M5X0.8-ST30	M5X0.8	60	16	5.5	4.5	7		
	M6X1.0-ST15	M6X1.0-ST30	M6X1.0	62	19	6.0	4.5	7		
4	M8X1.0-ST15	M8X1.0-ST30	M8X1.0	70	22	6.2	5.0	8	KH4	
	M8X1.25-ST15	M8X1.25-ST30	M8X1.25							
	M10X1.0-ST15	M10X1.0-ST30	M10X1.0	75	24	7.0	5.5	8		
	M10X1.25-ST15	M10X1.25-ST30	M10X1.25							
	M10X1.5-ST15	M10X1.5-ST30	M10X1.5							
	M12X1.0-ST15	M12X1.0-ST30	M12X1.0	82	29	8.5	6.5	9	KH5	
	M12X1.25-ST15	M12X1.25-ST30	M12X1.25							
	M12X1.5-ST15	M12X1.5-ST30	M12X1.5							
	M12X1.75-ST15	M12X1.75-ST30	M12X1.75							


※ It is ideal for mass tapping operations of general cast iron, ductile cast iron, brass-cast, thermosetting plastics, etc.

Applicable Workpiece Range

Carbon steel			Alloy steel	Quenched and tempered steel			Stainless steel	Tool steel	Cast steel	Cast iron	Ductile cast iron	Copper	Brass	Brass-cast	Bronze	Rolled aluminum	Aluminum-cast, alloyed	Magnesium-cast, alloyed	Zinc-cast, alloyed	Titanium alloy	Thermo-setting plastics	Thermo-plastics	
C -0.25%	C 0.25% -0.45%	C 0.45%-	SCM	25-45 HRC	45-55 HRC	50-60 HRC	SUS	SKD	SC	FC	FCD	Cu	Bs	BsC	PB	AI	AC ADC	MC	ZDC	Ti	Ni	-	-
										◎	○		○	○	○	○	○	○	○	○	○	○	○

Carbide Tap

ST type (Straight Tap)



(mm)

Flutes	Designation		Thread size	L (Overall length)	I (Thread length)	d (Shank diameter)	K (Square width)	Kl (Square length)	Limits	
	1.5P	3P								
3	M3X0.5-ST15	M3X0.5-ST30	M3X0.5	46	11	4.0	3.2	6	KH3	
	M4X0.7-ST15	M4X0.7-ST30	M4X0.7	52	13	5.0	4.0	7		
	M5X0.8-ST15	M5X0.8-ST30	M5X0.8	60	16	5.5	4.5	7		
	M6X1.0-ST15	M6X1.0-ST30	M6X1.0	62	19	6.0	4.5	7		
4	M8X1.0-ST15	M8X1.0-ST30	M8X1.0	70	22	6.2	5.0	8	KH4	
	M8X1.25-ST15	M8X1.25-ST30	M8X1.25							
	M10X1.0-ST15	M10X1.0-ST30	M10X1.0	75	24	7.0	5.5	8		
	M10X1.25-ST15	M10X1.25-ST30	M10X1.25							
	M10X1.5-ST15	M10X1.5-ST30	M10X1.5							
	M12X1.0-ST15	M12X1.0-ST30	M12X1.0	82	29	8.5	6.5	9	KH5	
	M12X1.25-ST15	M12X1.25-ST30	M12X1.25							
	M12X1.5-ST15	M12X1.5-ST30	M12X1.5							
	M12X1.75-ST15	M12X1.75-ST30	M12X1.75							

※ It is ideal for mass tapping operations of general cast iron, ductile cast iron, brass-cast, thermosetting plastics, etc.


※ Wear resistance was much improved by the use of TiCN coating for high efficiency tapping operations.

Applicable Workpiece Range

Carbon steel			Alloy steel	Quenched and tempered steel			Stainless steel	Tool steel	Cast steel	Cast iron	Ductile cast iron	Copper	Brass	Brass-cast	Bronze	Rolled aluminum	Aluminum-cast, alloyed	Magnesium-cast, alloyed	Zinc-cast, alloyed	Titanium alloy	Thermo-setting plastics	Thermo-plastics	
C	C0.25% -0.25%	C -0.45%	SCM	25-45 HRC	45-55 HRC	50-60 HRC	SUS	SKD	SC	FC	FCD	Cu	Bs	BsC	PB	AI	AC ADC	MC	ZDC	Ti	Ni	-	-
										◎	○		○	○	○	○	○	○	○	○	○	○	○

Carbide Tap

ST type (Straight Tap)



Helix Angle
0°

Carbide

TiN

Grade
PC20T

(mm)

Flutes	Designation		Thread size	L (Overall length)	I (Thread length)	d (Shank diameter)	K (Square width)	KI (Square length)	Limits
	1.5P	3P							
3	M3x0.5-ST15	M3x0.5-ST30	M3X0.5	46	11	4	3.2	6	KH3
	M4x0.7 -ST15	M4x0.7-ST30	M4X0.7	52	13	5	4	7	
	M5x0.8 -ST15	M5x0.8-ST30	M5X0.8	60	16	5.5	4.5	7	
	M6x1.0 -ST15	M6x1.0-ST30	M6X1.0	62	19	6	4.5	7	
4	M8x1.25 -ST15	M8x1.25-ST30	M8X1.25	70	22	6.2	5	8	KH4
	M10x1.5 -ST15	M10x1.5-ST30	M10X1.5	75	24	7	5.5	8	
	M12x1.75 -ST15	M12x1.75-ST30	M12X1.75	82	29	8.5	6.5	9	


※ It is ideal for mass tapping operations of general cast iron, ductile cast iron, brass-cast, thermosetting plastics, etc.

Applicable Workpiece Range

Carbon steel			Alloy steel	Quenched and tempered steel			Stainless steel	Tool steel	Cast steel	Cast iron	Ductile cast iron	Copper	Brass	Brass-cast	Bronze	Rolled aluminum	Aluminum-cast, alloyed	Magnesium-cast, alloyed	Zinc-cast, alloyed	Titanium alloy	Thermo-setting plastics	Thermo-plastics	
C -0.25%	C0.25% -0.45%	C 0.45%-	SCM	25-45 HRC	45-55 HRC	50-60 HRC	SUS	SKD	SC	FC	FCD	Cu	Bs	BsC	PB	Al	AC ADC	MC	ZDC	Ti	Ni	-	-
										◎	○		○	○	○	○		○	○	○		◎	

Carbide Tap

SP type (Spiral Tap)



		Helix Angle 15°	Carbide	Uncoated	Grade FN30T
--	--	--------------------	---------	----------	----------------

(mm)

Flutes	Designation		Thread size	L (Overall length)	I (Thread length)	d (Shank diameter)	K (Square width)	KI (Square length)	Limits	
	2.5P									
	M3X0.5-SP25	M3X0.5	2.5P	46	11	4.0	3.2	6	KH3	
	M4X0.7-SP25	M4X0.7		52	13	5.0	4.0	7		
	M5X0.8-SP25	M5X0.8		60	16	5.5	4.5	7		
	M6X1.0-SP25	M6X1.0		62	19	6.0	4.5	7		
	M8X1.0-SP25	M8X1.0	2.5P	70	22	6.2	5.0	8	KH4	
	M8X1.25-SP25	M8X1.25								
	M10X1.0-SP25	M10X1.0	2.5P	75	24	7.0	5.5	8		
	M10X1.25-SP25	M10X1.25								
	M10X1.5-SP25	M10X1.5								
	M12X1.0-SP25	M12X1.0	2.5P	82	29	8.5	6.5	9	KH5	
	M12X1.25-SP25	M12X1.25								
	M12X1.5-SP25	M12X1.5								
	M12X1.75-SP25	M12X1.75								


※ It is ideal for making blind holes in quantity on general cast iron, ductile cast iron, brass-cast, thermosetting plastics, etc.

Applicable Workpiece Range

Carbon steel			Alloy steel	Quenched and tempered steel			Stainless steel	Tool steel	Cast steel	Cast iron	Ductile cast iron	Copper	Brass	Brass-cast	Bronze	Rolled aluminum	Aluminum-cast, alloyed	Magnesium-cast, alloyed	Zinc-cast, alloyed	Titanium alloy	Thermo-setting plastics	Thermo-plastics	
C -0.25%	C0.25% -0.45%	C 0.45%-	SCM	25-45 HRC	45-55 HRC	50-60 HRC	SUS	SKD	SC	FC	FCD	Cu	Bs	BsC	PB	Al	AC ADC	MC	ZDC	Ti	Ni	-	-
										○	◎	○	○	○	○	○	○	○	○	○	○	○	

Carbide Tap

SP type (Spiral Tap)



(mm)

Flutes	Designation		Thread size	L (Overall length)	I (Thread length)	d (Shank diameter)	K (Square width)	KI (Square length)	Limits	
		2.5P								
3	M3X0.5-SP25	M3X0.5	2.5P	46	11	4.0	3.2	6	KH3	
	M4X0.7-SP25	M4X0.7		52	13	5.0	4.0	7		
	M5X0.8-SP25	M5X0.8		60	16	5.5	4.5	7		
	M6X1.0-SP25	M6X1.0		62	19	6.0	4.5	7		
4	M8X1.0-SP25	M8X1.0	2.5P	70	22	6.2	5.0	8	KH4	
	M8X1.25-SP25	M8X1.25								
	M10X1.0-SP25	M10X1.0		75	24	7.0	5.5	8		
	M10X1.25-SP25	M10X1.25								
	M10X1.5-SP25	M10X1.5								
	M12X1.0-SP25	M12X1.0	2.5P	82	29	8.5	6.5	9	KH5	
	M12X1.25-SP25	M12X1.25								
	M12X1.5-SP25	M12X1.5								
	M12X1.75-SP25	M12X1.75								

※ It is ideal for making blind holes in quantity on general cast iron, ductile cast iron, brass-cast, thermosetting plastics, etc.


※ Wear resistance was much improved by the use of TiCN coating for high efficiency tapping operations.

Applicable Workpiece Range

Carbon steel			Alloy steel	Quenched and tempered steel			Stainless steel	Tool steel	Cast steel	Cast iron	Ductile cast iron	Copper	Brass	Brass-cast	Bronze	Rolled aluminum	Aluminum-cast, alloyed	Magnesium-cast, alloyed	Zinc-cast, alloyed	Titanium alloy	Thermo-setting plastics	Thermo-plastics	
C -0.25%	C0.25% -0.45%	C 0.45%-	SCM	25-45 HRC	45-55 HRC	50-60 HRC	SUS	SKD	SC	FC	FCD	Cu	Bs	BsC	PB	AI	AC ADC	MC	ZDC	Ti	Ni	-	-
										○	○	○	○	○	○	○	○	○	○	○	○	○	

Carbide Tap

RT type (Roll Tap)



Carbide

Uncoated

Grade
FN30T

(mm)

Flutes	Designation			Thread size	L (Overall length)	I (Thread length)	d (Shank diameter)	K (Square width)	KI (Square length)	Limits
	2P	4P								
1	M3X0.5-RT20(S)	M3X0.5-RT40(S)		M3X0.5	46	11	4.0	3.2	6	GH5
4	M3X0.5-RT20(M)	M3X0.5-RT40(M)								
1	M4X0.7-RT20(S)	M4X0.7-RT40(S)		M4X0.7	52	13	5.0	4.0	7	GH6
4	M4X0.7-RT20(M)	M4X0.7-RT40(M)								
1	M5X0.8-RT20(S)	M5X0.8-RT40(S)		M5X0.8	60	16	5.5	4.5	7	
4	M5X0.8-RT20(M)	M5X0.8-RT40(M)								
1	M6X1.0-RT20(S)	M6X1.0-RT40(S)		M6X1.0	62	19	6.0	4.5	7	
4	M6X1.0-RT20(M)	M6X1.0-RT40(M)								
1	M8X1.25-RT20(S)	M8X1.25-RT40(S)		M8X1.25	70	22	6.2	5.0	8	
4	M8X1.25-RT20(M)	M8X1.25-RT40(M)								
1	M10X1.25-RT20(S)	M10X1.25-RT40(S)		M10X1.25	75	24	7.0	5.5	8	
4	M10X1.25-RT20(M)	M10X1.25-RT40(M)								
1	M12X1.0-RT20(S)	M12X1.0-RT40(S)		M12X1.0	82	29	8.5	6.5	9	GH7
4	M12X1.0-RT20(M)	M12X1.0-RT40(M)								
1	M12X1.25-RT20(S)	M12X1.25-RT40(S)		M12X1.25	82	29	8.5	6.5	9	
4	M12X1.25-RT20(M)	M12X1.25-RT40(M)								
1	M12X1.5-RT20(S)	M12X1.5-RT40(S)		M12X1.5	82	29	8.5	6.5	9	
4	M12X1.5-RT20(M)	M12X1.5-RT40(M)								
1	M12X1.75-RT20(S)	M12X1.75-RT40(S)		M12X1.75	82	29	8.5	6.5	9	GH8
4	M12X1.75-RT20(M)	M12X1.75-RT40(M)								


※ It is ideal for making both through holes and blind holes on non ferrous metals.

Applicable Workpiece Range

Carbon steel			Alloy steel	Quenched and tempered steel			Stain-less steel	Tool steel	Cast steel	Cast iron	Ductile cast iron	Copper	Brass	Brass-cast	Bronze	Rolled aluminum	Aluminum-cast, alloyed	Magnesium-cast, alloyed	Zinc-cast, alloyed	Titanium alloy	Thermo-setting plastics	Thermo-plastics	
C -0.25%	C -0.45%	C 0.45%-	SCM	25-45 HRC	45-55 HRC	50-60 HRC	SUS	SKD	SC	FC	FCD	Cu	Bs	BsC	PB	Al	AC ADC	MC	ZDC	Ti	Ni	-	-
												◎	◎	◎		◎	◎		◎				

Carbide Tap

RT type (Roll Tap)



Carbide	TiCN	Grade PC10T
---------	------	----------------

(mm)

Flutes	Designation		Thread size	L (Overall length)	I (Thread length)	d (Shank diameter)	K (Square width)	KI (Square length)	Limits
	2P	4P							
1	M3X0.5-RT20(S)	M3X0.5-RT40(S)	M3X0.5	46	11	4.0	3.2	6	GH5
4	M3X0.5-RT20(M)	M3X0.5-RT40(M)							
1	M4X0.7-RT20(S)	M4X0.7-RT40(S)	M4X0.7	52	13	5.0	4.0	7	GH6
4	M4X0.7-RT20(M)	M4X0.7-RT40(M)							
1	M5X0.8-RT20(S)	M5X0.8-RT40(S)	M5X0.8	60	16	5.5	4.5	7	
4	M5X0.8-RT20(M)	M5X0.8-RT40(M)							
1	M6X1.0-RT20(S)	M6X1.0-RT40(S)	M6X1.0	62	19	6.0	4.5	7	
4	M6X1.0-RT20(M)	M6X1.0-RT40(M)							
1	M8X1.25-RT20(S)	M8X1.25-RT40(S)	M8X1.25	70	22	6.2	5.0	8	
4	M8X1.25-RT20(M)	M8X1.25-RT40(M)							
1	M10X1.25-RT20(S)	M10X1.25-RT40(S)	M10X1.25	75	24	7.0	5.5	8	
4	M10X1.25-RT20(M)	M10X1.25-RT40(M)							
1	M12X1.0-RT20(S)	M12X1.0-RT40(S)	M12X1.0	82	29	8.5	6.5	9	
4	M12X1.0-RT20(M)	M12X1.0-RT40(M)							
1	M12X1.25-RT20(S)	M12X1.25-RT40(S)	M12X1.25	82	29	8.5	6.5	9	
4	M12X1.25-RT20(M)	M12X1.25-RT40(M)							
1	M12X1.5-RT20(S)	M12X1.5-RT40(S)	M12X1.5	82	29	8.5	6.5	9	
4	M12X1.5-RT20(M)	M12X1.5-RT40(M)							
1	M12X1.75-RT20(S)	M12X1.75-RT40(S)	M12X1.75	82	29	8.5	6.5	9	GH8
4	M12X1.75-RT20(M)	M12X1.75-RT40(M)							

※ It is for general use for both steels and non ferrous metal.


※ Wear resistance was much improved by the use of TiCN coating for high efficiency tapping operations.

Applicable Workpiece Range

Carbon steel			Alloy steel	Quenched and tempered steel			Stain-less steel	Tool steel	Cast steel	Cast iron	Ductile cast iron	Copper	Brass	Brass-cast	Bronze	Rolled aluminum	Aluminum-cast, alloyed	Magnesium-cast, alloyed	Zinc-cast, alloyed	Titanium alloy	Thermo-setting plastics	Thermo-plastics	
C -0.25%	C -0.45%	C 0.45%-	SCM	25-45 HRC	45-55 HRC	50-60 HRC	SUS	SKD	SC	FC	FCD	Cu	Bs	BsC	PB	Al	AC ADC	MC	ZDC	Ti	Ni	-	-
◎	◎	○	○				◎					◎	◎	◎			◎	◎					

Carbide Tap

SR type (Spiral Roll Tap)



Carbide

Uncoated

Grade
FN30T

(mm)

Designation		Thread size	L (Overall length)	I (Thread length)	d (Shank diameter)	K (Square width)	KI (Square length)	Limits
2P	4P							
M3X0.5-SR20	M3X0.5-SR40	M3X0.5	46	18	4.0	3.2	6	GH6
M3.5X0.6-SR20	M3.5X0.6-SR40	M3.5X0.6						
M4X0.7-SR20	M4X0.7-SR40	M4X0.7	52	20	5.0	4.0	7	GH7
M5X0.8-SR20	M5X0.8-SR40	M5X0.8	60	22	5.5	4.5	7	
M6X1.0-SR20	M6X1.0-SR40	M6X1.0	62	24	6.0	4.5	7	


※ It is for general use for tapping aluminum, magnesium and zinc as well as non ferrous metal.

Applicable Workpiece Range

Carbon steel			Alloy steel	Quenched and tempered steel			Stainless steel	Tool steel	Cast steel	Cast iron	Ductile cast iron	Copper	Brass	Brass-cast	Bronze	Rolled aluminum	Aluminum-cast, alloyed	Magnesium-cast, alloyed	Zinc-cast, alloyed	Titanium alloy	Thermo-setting plastics	Thermoplastics	
C -0.25%	C0.25% -0.45%	C 0.45%-	SCM	25-45 HRC	45-55 HRC	50-60 HRC	SUS	SKD	SC	FC	FCD	Cu	Bs	BsC	PB	Al	AC ADC	MC	ZDC	Ti	Ni	-	-
												◎	◎	◎		◎	◎		◎				

Carbide Tap

SR type (Spiral Roll Tap)



Carbide

TiCN

Grade
PC10T

(mm)

Designation		Thread size	L (Overall length)	I (Thread length)	d (Shank diameter)	K (Square width)	KI (Square length)	Limits
2P	4P							
M3X0.5-SR20	M3X0.5-SR40	M3X0.5	46	18	4.0	3.2	6	GH6
M3.5X0.6-SR20	M3.5X0.6-SR40	M3.5X0.6						
M4X0.7-SR20	M4X0.7-SR40	M4X0.7	52	20	5.0	4.0	7	GH7
M5X0.8-SR20	M5X0.8-SR40	M5X0.8	60	22	5.5	4.5	7	
M6X1.0-SR20	M6X1.0-SR40	M6X1.0	62	24	6.0	4.5	7	

※ It is ideal for tapping steel, non ferrous metal and stainless steel.


※ Wear resistance was much improved by the use of TiCN coating for high efficiency tapping operations.

Applicable Workpiece Range

Carbon steel			Alloy steel	Quenched and tempered steel			Stainless steel	Tool steel	Cast steel	Cast iron	Ductile cast iron	Copper	Brass	Brass-cast	Bronze	Rolled aluminum	Aluminum-cast, alloyed	Magnesium-cast, alloyed	Zinc-cast, alloyed	Titanium alloy	Thermo-setting plastics	Thermo-plastics	
C -0.25%	C 0.25% -0.45%	C 0.45%-	SCM	25-45 HRC	45-55 HRC	50-60 HRC	SUS	SKD	SC	FC	FCD	Cu	Bs	BsC	PB	Al	AC ADC	MC	ZDC	Ti	Ni	-	-
◎	◎	○	○				◎					◎	◎	◎		◎	◎		◎				

HSS Tap

ST type (Straight Tap)



Helix Angle
0°

HSSE

Uncoated

Grade
HN30T

(mm)

Flutes	Designation			Thread size	L (Overall length)	l (Thread length)	d (Shank diameter)	K (Square width)	Kl (Square length)	Limits
	1.5P	3P	5P							
	M3X0.5-ST15	M3X0.5-ST30	M3X0.5-ST50	M3X0.5	46	11	4.0	3.2	6	KH2
	M4X0.7-ST15	M4X0.7-ST30	M4X0.7-ST50	M4X0.7	52	13	5.0	4.0	7	
	M5X0.8-ST15	M5X0.8-ST30	M5X0.8-ST50	M5X0.8	60	16	5.5	4.5	7	
	M6X1.0-ST15	M6X1.0-ST30	M6X1.0-ST50	M6X1.0	62	19	6.0	4.5	7	
	M8X1.25-ST15	M8X1.25-ST30	M8X1.25-ST50	M8X1.25	70	22	6.2	5.0	8	KH2
	M10X1.25-ST15	M10X1.25-ST30	M10X1.25-ST50	M10X1.25	75	24	7.0	5.5	8	
	M10X1.5-ST15	M10X1.5-ST30	M10X1.5-ST50	M10X1.5	75	24	7.0	5.5	8	
	M12X1.0-ST15	M12X1.0-ST30	M12X1.0-ST50	M12X1.0	82	29	8.5	6.5	9	KH2
	M12X1.25-ST15	M12X1.25-ST30	M12X1.25-ST50	M12X1.25	82	29	8.5	6.5	9	
	M12X1.5-ST15	M12X1.5-ST30	M12X1.5-ST50	M12X1.5	82	29	8.5	6.5	9	
	M12X1.75-ST15	M12X1.75-ST30	M12X1.75-ST50	M12X1.75	82	29	8.5	6.5	9	
	M14X1.5-ST15	M14X1.5-ST30	M14X1.5-ST50	M14X1.5	88	30	10.5	8.0	11	KH3
	M14X2.0-ST15	M14X2.0-ST30	M14X2.0-ST50	M14X2.0	88	30	10.5	8.0	11	
	M16X1.5-ST15	M16X1.5-ST30	M16X1.5-ST50	M16X1.5	95	32	12.5	10.0	13	
	M16X2.0-ST15	M16X2.0-ST30	M16X2.0-ST50	M16X2.0	95	32	12.5	10.0	13	
	M18X1.5-ST15	M18X1.5-ST30	M18X1.5-ST50	M18X1.5	100	37	14.0	11.0	14	KH3
	M18X2.5-ST15	M18X2.5-ST30	M18X2.5-ST50	M18X2.5	100	37	14.0	11.0	14	
	M20X1.5-ST15	M20X1.5-ST30	M20X1.5-ST50	M20X1.5	105	37	15.0	12.0	15	
	M20X2.5-ST15	M20X2.5-ST30	M20X2.5-ST50	M20X2.5	105	37	15.0	12.0	15	


※ It is ideal for tapping general cast iron, medium cast iron and non ferrous metal.

Applicable Workpiece Range

Carbon steel			Alloy steel	Quenched and tempered steel			Stainless steel	Tool steel	Cast steel	Cast iron	Ductile cast iron	Copper	Brass	Brass-cast	Bronze	Rolled aluminum	Aluminum-cast, alloyed	Magnesium-cast, alloyed	Zinc-cast, alloyed	Titanium alloy	Thermo-setting plastics	Thermoplastics	
C -0.25%	C0.25% -0.45%	C 0.45%-	SCM	25-45 HRC	45-55 HRC	50-60 HRC	SUS	SKD	SC	FC	FCD	Cu	Bs	BsC	PB	AI	AC ADC	MC	ZDC	Ti	Ni	-	-
	O										O		O	O	O	O	O	O	O	O			

HSS Tap

ST type (Straight Tap)



(mm)

Flutes	Designation			Thread size	L (Overall length)	l (Thread length)	d (Shank diameter)	K (Square width)	Kl (Square length)	Limits
	1.5P	3P	5P							
3	M3X0.5-ST15	M3X0.5-ST30	M3X0.5-ST50	M3X0.5	46	11	4.0	3.2	6	KH2
	M4X0.7-ST15	M4X0.7-ST30	M4X0.7-ST50	M4X0.7	52	13	5.0	4.0	7	
	M5X0.8-ST15	M5X0.8-ST30	M5X0.8-ST50	M5X0.8	60	16	5.5	4.5	7	
	M6X1.0-ST15	M6X1.0-ST30	M6X1.0-ST50	M6X1.0	62	19	6.0	4.5	7	
4	M8X1.25-ST15	M8X1.25-ST30	M8X1.25-ST50	M8X1.25	70	22	6.2	5.0	8	KH2
	M10X1.25-ST15	M10X1.25-ST30	M10X1.25-ST50	M10X1.25	75	24	7.0	5.5	8	
	M10X1.5-ST15	M10X1.5-ST30	M10X1.5-ST50	M10X1.5	75	24	7.0	5.5	8	
	M12X1.0-ST15	M12X1.0-ST30	M12X1.0-ST50	M12X1.0	82	29	8.5	6.5	9	
	M12X1.25-ST15	M12X1.25-ST30	M12X1.25-ST50	M12X1.25	82	29	8.5	6.5	9	
	M12X1.5-ST15	M12X1.5-ST30	M12X1.5-ST50	M12X1.5	82	29	8.5	6.5	9	KH3
	M12X1.75-ST15	M12X1.75-ST30	M12X1.75-ST50	M12X1.75	82	29	8.5	6.5	9	
	M14X1.5-ST15	M14X1.5-ST30	M14X1.5-ST50	M14X1.5	88	30	10.5	8.0	11	
	M14X2.0-ST15	M14X2.0-ST30	M14X2.0-ST50	M14X2.0	88	30	10.5	8.0	11	
	M16X1.5-ST15	M16X1.5-ST30	M16X1.5-ST50	M16X1.5	95	32	12.5	10.0	13	
	M16X2.0-ST15	M16X2.0-ST30	M16X2.0-ST50	M16X2.0	95	32	12.5	10.0	13	
	M18X1.5-ST15	M18X1.5-ST30	M18X1.5-ST50	M18X1.5	100	37	14.0	11.0	14	KH3
	M18X2.5-ST15	M18X2.5-ST30	M18X2.5-ST50	M18X2.5	100	37	14.0	11.0	14	
	M20X1.5-ST15	M20X1.5-ST30	M20X1.5-ST50	M20X1.5	105	37	15.0	12.0	15	
	M20X2.5-ST15	M20X2.5-ST30	M20X2.5-ST50	M20X2.5	105	37	15.0	12.0	15	

※ It is ideal for making both through holes and blind holes on carbon steel, alloy steel and non ferrous metal.


※ Wear resistance was much improved by the use of TiCN coating for high efficiency tapping operations.

Applicable Workpiece Range

Carbon steel			Alloy steel	Quenched and tempered steel			Stainless steel	Tool steel	Cast steel	Cast iron	Ductile cast iron	Copper	Brass	Brass-cast	Bronze	Rolled aluminum	Aluminum-cast, alloyed	Magnesium-cast, alloyed	Zinc-cast, alloyed	Titanium alloy	Thermo-setting plastics	Thermoplastics	
C	C0.25% -0.45%	C 0.45%-	SCM	25-45 HRC	45-55 HRC	50-60 HRC	SUS	SKD	SC	FC	FCD	Cu	Bs	BsC	PB	AI	AC ADC	MC	ZDC	Ti	Ni	-	-
O	O	O	O	O								O	O	O	O	O	O	O	O				

HSS Tap

ST type (Straight Tap)



(mm)

Flutes	Designation			Thread size	L (Overall length)	l (Thread length)	d (Shank diameter)	K (Square width)	Kl (Square length)	Limits
	1.5P	3P	5P							
3	M3X0.5-ST15	M3X0.5-ST30	M3X0.5-ST50	M3X0.5	46	11	4.0	3.2	6	KH2
	M4X0.7-ST15	M4X0.7-ST30	M4X0.7-ST50	M4X0.7	52	13	5.0	4.0	7	
	M5X0.8-ST15	M5X0.8-ST30	M5X0.8-ST50	M5X0.8	60	16	5.5	4.5	7	
	M6X1.0-ST15	M6X1.0-ST30	M6X1.0-ST50	M6X1.0	62	19	6.0	4.5	7	
4	M8X1.25-ST15	M8X1.25-ST30	M8X1.25-ST50	M8X1.25	70	22	6.2	5.0	8	KH2
	M10X1.25-ST15	M10X1.25-ST30	M10X1.25-ST50	M10X1.25	75	24	7.0	5.5	8	
	M10X1.5-ST15	M10X1.5-ST30	M10X1.5-ST50	M10X1.5	75	24	7.0	5.5	8	
	M12X1.0-ST15	M12X1.0-ST30	M12X1.0-ST50	M12X1.0	82	29	8.5	6.5	9	
	M12X1.25-ST15	M12X1.25-ST30	M12X1.25-ST50	M12X1.25	82	29	8.5	6.5	9	
	M12X1.5-ST15	M12X1.5-ST30	M12X1.5-ST50	M12X1.5	82	29	8.5	6.5	9	KH2
	M12X1.75-ST15	M12X1.75-ST30	M12X1.75-ST50	M12X1.75	82	29	8.5	6.5	9	
	M14X1.5-ST15	M14X1.5-ST30	M14X1.5-ST50	M14X1.5	88	30	10.5	8.0	11	
	M14X2.0-ST15	M14X2.0-ST30	M14X2.0-ST50	M14X2.0	88	30	10.5	8.0	11	
	M16X1.5-ST15	M16X1.5-ST30	M16X1.5-ST50	M16X1.5	95	32	12.5	10.0	13	
	M16X2.0-ST15	M16X2.0-ST30	M16X2.0-ST50	M16X2.0	95	32	12.5	10.0	13	
	M18X1.5-ST15	M18X1.5-ST30	M18X1.5-ST50	M18X1.5	100	37	14.0	11.0	14	KH3
	M18X2.5-ST15	M18X2.5-ST30	M18X2.5-ST50	M18X2.5	100	37	14.0	11.0	14	
	M20X1.5-ST15	M20X1.5-ST30	M20X1.5-ST50	M20X1.5	105	37	15.0	12.0	15	
	M20X2.5-ST15	M20X2.5-ST30	M20X2.5-ST50	M20X2.5	105	37	15.0	12.0	15	

※ It is ideal for making both through holes and blind holes on carbon steel, alloy steel and non ferrous metal.


※ Wear resistance was much improved by the use of TiCN coating for high efficiency tapping operations.

Applicable Workpiece Range

Carbon steel			Alloy steel	Quenched and tempered steel			Stainless steel	Tool steel	Cast steel	Cast iron	Ductile cast iron	Copper	Brass	Brass-cast	Bronze	Rolled aluminum	Aluminum-cast, alloyed	Magnesium-cast, alloyed	Zinc-cast, alloyed	Titanium alloy	Thermo-setting plastics	Thermoplastics	
C -0.25%	C -0.45%	C 0.45%-	SCM	25-45 HRC	45-55 HRC	50-60 HRC	SUS	SKD	SC	FC	FCD	Cu	Bs	BsC	PB	AI	AC ADC	MC	ZDC	Ti	Ni	-	-
○	○	○	○	○								○	○	○	○	○	○	○	○	○			

HSS Tap

ST type (Straight Tap)



Helix Angle
0°

HSSE

HOMO

Grade
HH30T

(mm)

Flutes	Designation		Thread size	L (Overall length)	I (Thread length)	d (Shank diameter)	K (Square width)	KI (Square length)	Limits
	1.5P	5P							
4	M8x1.25-ST15	M8x1.25-ST50	M8x1.25	70	22	6.2	5	8	KH2
	-	M14x2.0-ST50	M14x2.0	88	30	10.5	8	11	KH3
	M16x2.0-ST15	-	M16x2.0	95	32	12.5	10	13	

※ Built-up edges are prevented due to the reduced coefficient of friction by using porous cutting fluid of Fe304.


※ It is ideal for tapping SUS, cast steel, carbon steel for machine structure, etc.

Applicable Workpiece Range

Carbon steel			Alloy steel	Quenched and tempered steel			Stainless steel	Tool steel	Cast steel	Cast iron	Ductile cast iron	Copper	Brass	Brass-cast	Bronze	Rolled aluminum	Aluminum-cast, alloyed	Magnesium-cast, alloyed	Zinc-cast, alloyed	Titanium alloy	Thermo-setting plastics	Thermoplastics	
C -0.25%	C0.25% -0.45%	C 0.45%-	SCM	25-45 HRC	45-55 HRC	50-60 HRC	SUS	SKD	SC	FC	FCD	Cu	Bs	BsC	PB	AI	AC ADC	MC	ZDC	Ti	Ni	-	-
◎	◎	◎	◎	◎	◎	◎	○	○	○	○	○												

HSS Tap

PT type (Point Tap)



(mm)

Flutes	Designation		Thread size	L (Overall length)	I (Thread length)	d (Shank diameter)	K (Square width)	Kl (Square length)	Limits
	5P								
3	M3X0.5-PT50	M3X0.5	46	11	4.0	3.2	6		KH2
	M4X0.7-PT50	M4X0.7	52	13	5.0	4.0	7		
	M5X0.8-PT50	M5X0.8	60	16	5.5	4.5	7		
	M6X1.0-PT50	M6X1.0	62	19	6.0	4.5	7		
4	M8X1.25-PT50	M8X1.25	70	22	6.2	5.0	8		KH3
	M10X1.25-PT50	M10X1.25	75	24	7.0	5.5	8		
	M10X1.5-PT50	M10X1.5	75	24	7.0	5.5	8		
	M12X1.0-PT50	M12X1.0	82	29	8.5	6.5	9		
	M12X1.25-PT50	M12X1.25	82	29	8.5	6.5	9		KH4
	M12X1.5-PT50	M12X1.5	82	29	8.5	6.5	9		
	M12X1.75-PT50	M12X1.75	82	29	8.5	6.5	9		
	M14X1.5-PT50	M14X1.5	88	30	10.5	8.0	11		
	M14X2.0-PT50	M14X2.0	88	30	10.5	8.0	11		KH4
	M16X1.5-PT50	M16X1.5	95	32	12.5	10.0	13		
	M16X2.0-PT50	M16X2.0	95	32	12.5	10.0	13		
	M18X1.5-PT50	M18X1.5	100	37	14.0	11.0	14		KH4
	M18X2.5-PT50	M18X2.5	100	37	14.0	11.0	14		
	M20X1.5-PT50	M20X1.5	105	37	15.0	12.0	15		
	M20X2.5-PT50	M20X2.5	105	37	15.0	12.0	15		


※ It is ideal for making through holes on carbon steel, alloy steel and non ferrous metal.

Applicable Workpiece Range

Carbon steel			Alloy steel	Quenched and tempered steel			Stainless steel	Tool steel	Cast steel	Cast iron	Ductile cast iron	Copper	Brass	Brass-cast	Bronze	Rolled aluminum	Aluminum-cast, alloyed	Magnesium-cast, alloyed	Zinc-cast, alloyed	Titanium alloy	Thermo-setting plastics	Thermo-plastics	
C -0.25%	C0.25% -0.45%	C 0.45%-	SCM	25-45 HRC	45-55 HRC	50-60 HRC	SUS	SKD	SC	FC	FCD	Cu	Bs	BsC	PB	Al	AC ADC	MC	ZDC	Ti	Ni	-	-
○	○	○	◎								○	○	○	○	○	○	○	○	○	○	○	○	

HSS Tap

PT type (Point Tap)



Helix Angle
0°

HSSE

TiN

Grade
HC20T

(mm)

Flutes	Designation		Thread size	L (Overall length)	I (Thread length)	d (Shank diameter)	K (Square width)	Kl (Square length)	Limits
	5P								
	M3X0.5-PT50	M3X0.5	46	11	4.0	3.2	6		KH2
	M4X0.7-PT50	M4X0.7	52	13	5.0	4.0	7		
	M5X0.8-PT50	M5X0.8	60	16	5.5	4.5	7		
	M6X1.0-PT50	M6X1.0	62	19	6.0	4.5	7		
	M8X1.25-PT50	M8X1.25	70	22	6.2	5.0	8		KH3
	M10X1.25-PT50	M10X1.25	75	24	7.0	5.5	8		
	M10X1.5-PT50	M10X1.5	75	24	7.0	5.5	8		
	M12X1.0-PT50	M12X1.0	82	29	8.5	6.5	9		
	M12X1.25-PT50	M12X1.25	82	29	8.5	6.5	9		KH4
	M12X1.5-PT50	M12X1.5	82	29	8.5	6.5	9		
	M12X1.75-PT50	M12X1.75	82	29	8.5	6.5	9		
	M14X1.5-PT50	M14X1.5	88	30	10.5	8.0	11		
	M14X2.0-PT50	M14X2.0	88	30	10.5	8.0	11		KH4
	M16X1.5-PT50	M16X1.5	95	32	12.5	10.0	13		
	M16X2.0-PT50	M16X2.0	95	32	12.5	10.0	13		
	M18X1.5-PT50	M18X1.5	100	37	14.0	11.0	14		KH4
	M18X2.5-PT50	M18X2.5	100	37	14.0	11.0	14		
	M20X1.5-PT50	M20X1.5	105	37	15.0	12.0	15		
	M20X2.5-PT50	M20X2.5	105	37	15.0	12.0	15		

※ It is ideal for making through holes on carbon steel, alloy steel and non ferrous metal.


※ Wear resistance was much improved by the use of TiN coating for high efficiency tapping operations.

Applicable Workpiece Range

Carbon steel			Alloy steel	Quenched and tempered steel			Stainless steel	Tool steel	Cast steel	Cast iron	Ductile cast iron	Copper	Brass	Brass-cast	Bronze	Rolled aluminum	Aluminum-cast, alloyed	Magnesium-cast, alloyed	Zinc-cast, alloyed	Titanium alloy	Thermo-setting plastics	Thermo-plastics	
C -0.25%	C 0.25% -0.45%	C 0.45% -	SCM	25-45 HRC	45-55 HRC	50-60 HRC	SUS	SKD	SC	FC	FCD	Cu	Bs	BsC	PB	Al	AC ADC	MC	ZDC	Ti	Ni	-	-
○	○	○	○				◎	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○

HSS Tap

PT type (Point Tap)



(mm)

Flutes	Designation		Thread size	L (Overall length)	I (Thread length)	d (Shank diameter)	K (Square width)	Kl (Square length)	Limits
	5P								
3	M3X0.5-PT50	M3X0.5	46	11	4.0	3.2	6		KH2
	M4X0.7-PT50	M4X0.7	52	13	5.0	4.0	7		
	M5X0.8-PT50	M5X0.8	60	16	5.5	4.5	7		
	M6X1.0-PT50	M6X1.0	62	19	6.0	4.5	7		
4	M8X1.25-PT50	M8X1.25	70	22	6.2	5.0	8		KH3
	M10X1.25-PT50	M10X1.25	75	24	7.0	5.5	8		
	M10X1.5-PT50	M10X1.5	75	24	7.0	5.5	8		
	M12X1.0-PT50	M12X1.0	82	29	8.5	6.5	9		
	M12X1.25-PT50	M12X1.25	82	29	8.5	6.5	9		KH4
	M12X1.5-PT50	M12X1.5	82	29	8.5	6.5	9		
	M12X1.75-PT50	M12X1.75	82	29	8.5	6.5	9		
	M14X1.5-PT50	M14X1.5	88	30	10.5	8.0	11		
	M14X2.0-PT50	M14X2.0	88	30	10.5	8.0	11		KH4
	M16X1.5-PT50	M16X1.5	95	32	12.5	10.0	13		
	M16X2.0-PT50	M16X2.0	95	32	12.5	10.0	13		
	M18X1.5-PT50	M18X1.5	100	37	14.0	11.0	14		KH4
	M18X2.5-PT50	M18X2.5	100	37	14.0	11.0	14		
	M20X1.5-PT50	M20X1.5	105	37	15.0	12.0	15		
	M20X2.5-PT50	M20X2.5	105	37	15.0	12.0	15		

※ It is ideal for making through holes on carbon steel, alloy steel and non ferrous metal.


※ Wear resistance was much improved by the use of TiN coating for high efficiency tapping operations.

Applicable Workpiece Range

Carbon steel			Alloy steel	Quenched and tempered steel			Stainless steel	Tool steel	Cast steel	Cast iron	Ductile cast iron	Copper	Brass	Brass-cast	Bronze	Rolled aluminum	Aluminum-cast, alloyed	Magnesium-cast, alloyed	Zinc-cast, alloyed	Titanium alloy	Thermo-setting plastics	Thermo-plastics	
C -0.25%	C 0.25% -0.45%	C 0.45% -	SCM	25-45 HRC	45-55 HRC	50-60 HRC	SUS	SKD	SC	FC	FCD	Cu	Bs	BsC	PB	Al	AC ADC	MC	ZDC	Ti	Ni	-	-
◎	◎	◎	○				○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	

HSS Tap

PT type (Point Tap)



(mm)

Flutes	Designation		Thread size	L (Overall length)	I (Thread length)	d (Shank diameter)	K (Square width)	KI (Square length)	Limits
	5P								
3	M3X0.5-PT50		M3x0.5	46	11	4	3.2	6	KH2
	M4X0.7-PT50		M4x0.7	52	13	5	4	7	
	M5X0.8-PT50		M5x0.8	60	16	5.5	4.5	7	
	M6X1.0-PT50		M6x1.0	62	19	6	4.5	7	
4	M8X1.25-PT50		M8x1.25	70	22	6.2	5	8	KH3
	M10X1.25-PT50		M10x1.25	75	24	7	5.5	8	
	M10X1.5-PT50		M10x1.5	75	24	7	5.5	8	
	M12X1.0-PT50		M12x1.0	82	29	8.5	6.5	9	
	M12X1.25-PT50		M12x1.25	82	29	8.5	6.5	9	KH4
	M12X1.5-PT50		M12x1.5	82	29	8.5	6.5	9	
	M12X1.75-PT50		M12x1.75	82	29	8.5	6.5	9	
	M14X1.5-PT50		M14x1.5	88	30	10.5	8	11	
	M14X2.0-PT50		M14x2.0	88	30	10.5	8	11	
	M16X1.5-PT50		M16x1.5	95	32	12.5	10	13	KH3
	M16X2.0-PT50		M16x2.0	95	32	12.5	10	13	
	M18X1.5-PT50		M18x1.5	100	37	14	11	14	
	M18X2.5-PT50		M18x2.5	100	37	14	11	14	
	M20X1.5-PT50		M20x1.5	105	37	15	12	15	KH4
	M20X2.5-PT50		M20x2.5	105	37	15	12	15	

※ Built-up edges are prevented due to the reduced coefficient of friction by using porous cutting fluid of Fe^3O_4 .


※ It is ideal for tapping SUS, cast steel, carbon steel for machine structure, etc.

Applicable Workpiece Range

Carbon steel			Alloy steel	Quenched and tempered steel			Stainless steel	Tool steel	Cast steel	Cast iron	Ductile cast iron	Copper	Brass	Brass-cast	Bronze	Rolled aluminum	Aluminum-cast, alloyed	Magnesium-cast, alloyed	Zinc-cast, alloyed	Titanium alloy	Thermo-setting plastics	Thermo-plastics	
C -0.25%	C 0.25% -0.45%	C 0.45% -	SCM	25-45 HRC	45-55 HRC	50-60 HRC	SUS	SKD	SC	FC	FCD	Cu	Bs	BsC	PB	Al	AC ADC	MC	ZDC	Ti	Ni	-	-
◎	◎	◎	◎	◎	◎	◎	○	○	○	○	○												

HSS Tap

SP type (Spiral Tap)



(mm)

Flutes	Designation		Thread size 2.5P	L (Overall length)	I (Thread length)	d (Shank diameter)	K (Square width)	Kl (Square length)	Limits
	3	4							
3	M3X0.5-SP25	M3X0.5	46	11	4.0	3.2	6		KH2
	M4X0.7-SP25	M4X0.7	52	13	5.0	4.0	7		
	M5X0.8-SP25	M5X0.8	60	16	5.5	4.5	7		
	M6X1.0-SP25	M6X1.0	62	19	6.0	4.5	7		
	M8X1.25-SP25	M8X1.25	70	22	6.2	5.0	8		
	M10X1.25-SP25	M10X1.25	75	24	7.0	5.5	8		
	M10X1.5-SP25	M10X1.5	75	24	7.0	5.5	8		
	M12X1.0-SP25	M12X1.0	82	29	8.5	6.5	9		
	M12X1.25-SP25	M12X1.25	82	29	8.5	6.5	9		
	M12X1.5-SP25	M12X1.5	82	29	8.5	6.5	9		
	M12X1.75-SP25	M12X1.75	82	29	8.5	6.5	9		
	M14X1.5-SP25	M14X1.5	88	30	10.5	8.0	11		
	M14X2.0-SP25	M14X2.0	88	30	10.5	8.0	11		
4	M16X1.5-SP25	M16X1.5	95	32	12.5	10.0	13		KH3
	M16X2.0-SP25	M16X2.0	95	32	12.5	10.0	13		
	M18X1.5-SP25	M18X1.5	100	37	14.0	11.0	14		
	M18X2.5-SP25	M18X2.5	100	37	14.0	11.0	14		
	M20X1.5-SP25	M20X1.5	105	37	15.0	12.0	15		KH3
	M20X2.5-SP25	M20X2.5	105	37	15.0	12.0	15		


※ It is ideal for making blind holes and its flutes provide excellent chip evacuation in tapping carbon steel, alloy steel and non ferrous metal.

Applicable Workpiece Range

Carbon steel			Alloy steel	Quenched and tempered steel			Stainless steel	Tool steel	Cast steel	Cast iron	Ductile cast iron	Copper	Brass	Brass-cast	Bronze	Rolled aluminum	Aluminum-cast, alloyed	Magnesium-cast, alloyed	Zinc-cast, alloyed	Titanium alloy	Thermo-setting plastics	Thermo-plastics	
C -0.25%	C0.25% -0.45%	C 0.45%-	SCM	25-45 HRC	45-55 HRC	50-60 HRC	SUS	SKD	SC	FC	FCD	Cu	Bs	BsC	PB	Al	AC ADC	MC	ZDC	Ti	Ni	-	-
	O		◎								O	O	O	O	O	O	O	O	O	O	O	O	

HSS Tap

SP type (Spiral Tap)



Helix Angle
35°

HSSE

TiN

Grade
HC20T

(mm)

Flutes	Designation		Thread size	L (Overall length)	I (Thread length)	d (Shank diameter)	K (Square width)	KI (Square length)	Limits
	2.5P								
	M3X0.5-SP25	M3X0.5	46	11	4.0	3.2	6		KH2
	M4X0.7-SP25	M4X0.7	52	13	5.0	4.0	7		
	M5X0.8-SP25	M5X0.8	60	16	5.5	4.5	7		
	M6X1.0-SP25	M6X1.0	62	19	6.0	4.5	7		
	M8X1.25-SP25	M8X1.25	70	22	6.2	5.0	8		
	M10X1.25-SP25	M10X1.25	75	24	7.0	5.5	8		
	M10X1.5-SP25	M10X1.5	75	24	7.0	5.5	8		
	M12X1.0-SP25	M12X1.0	82	29	8.5	6.5	9		
	M12X1.25-SP25	M12X1.25	82	29	8.5	6.5	9		
	M12X1.5-SP25	M12X1.5	82	29	8.5	6.5	9		
	M12X1.75-SP25	M12X1.75	82	29	8.5	6.5	9		
	M14X1.5-SP25	M14X1.5	88	30	10.5	8.0	11		
	M14X2.0-SP25	M14X2.0	88	30	10.5	8.0	11		
	M16X1.5-SP25	M16X1.5	95	32	12.5	10.0	13		KH3
	M16X2.0-SP25	M16X2.0	95	32	12.5	10.0	13		
	M18X1.5-SP25	M18X1.5	100	37	14.0	11.0	14		
	M18X2.5-SP25	M18X2.5	100	37	14.0	11.0	14		
	M20X1.5-SP25	M20X1.5	105	37	15.0	12.0	15		KH3
	M20X2.5-SP25	M20X2.5	105	37	15.0	12.0	15		

※ It is ideal for making blind holes and its flutes provide excellent chip evacuation in tapping carbon steel, alloy steel and non ferrous metal.


※ Wear resistance was much improved by the use of TiN coating for high efficiency tapping operations.

Applicable Workpiece Range

Carbon steel			Alloy steel	Quenched and tempered steel			Stainless steel	Tool steel	Cast steel	Cast iron	Ductile cast iron	Copper	Brass	Brass-cast	Bronze	Rolled aluminum	Aluminum-cast, alloyed	Magnesium-cast, alloyed	Zinc-cast, alloyed	Titanium alloy	Thermo-setting plastics	Thermo-plastics	
C -0.25%	C0.25% -0.45%	C 0.45%-	SCM	25-45 HRC	45-55 HRC	50-60 HRC	SUS	SKD	SC	FC	FCD	Cu	Bs	BsC	PB	Al	AC ADC	MC	ZDC	Ti	Ni	-	-
○	○	○	○				○	○	○		○	○	○	○	○	○	○	○	○	○	○	○	

HSS Tap

SP type (Spiral Tap)



(mm)

Flutes	Designation		Thread size	L (Overall length)	I (Thread length)	d (Shank diameter)	K (Square width)	Kl (Square length)	Limits
	2.5P								
	M3X0.5-SP25	M3X0.5	46	11	4.0	3.2	6		KH2
	M4X0.7-SP25	M4X0.7	52	13	5.0	4.0	7		
	M5X0.8-SP25	M5X0.8	60	16	5.5	4.5	7		
	M6X1.0-SP25	M6X1.0	62	19	6.0	4.5	7		
	M8X1.25-SP25	M8X1.25	70	22	6.2	5.0	8		
	M10X1.25-SP25	M10X1.25	75	24	7.0	5.5	8		
	M10X1.5-SP25	M10X1.5	75	24	7.0	5.5	8		
	M12X1.0-SP25	M12X1.0	82	29	8.5	6.5	9		
	M12X1.25-SP25	M12X1.25	82	29	8.5	6.5	9		
	M12X1.5-SP25	M12X1.5	82	29	8.5	6.5	9		
	M12X1.75-SP25	M12X1.75	82	29	8.5	6.5	9		
	M14X1.5-SP25	M14X1.5	88	30	10.5	8.0	11		
	M14X2.0-SP25	M14X2.0	88	30	10.5	8.0	11		
	M16X1.5-SP25	M16X1.5	95	32	12.5	10.0	13		KH3
	M16X2.0-SP25	M16X2.0	95	32	12.5	10.0	13		
	M18X1.5-SP25	M18X1.5	100	37	14.0	11.0	14		
	M18X2.5-SP25	M18X2.5	100	37	14.0	11.0	14		
	M20X1.5-SP25	M20X1.5	105	37	15.0	12.0	15		KH3
	M20X2.5-SP25	M20X2.5	105	37	15.0	12.0	15		

※ It is ideal for making blind holes and its flutes provide excellent chip evacuation in tapping carbon steel, alloy steel and non ferrous metal.


※ Wear resistance was much improved by the use of TiCN coating for high efficiency tapping operations.

Applicable Workpiece Range

Carbon steel			Alloy steel	Quenched and tempered steel			Stainless steel	Tool steel	Cast steel	Cast iron	Ductile cast iron	Copper	Brass	Brass-cast	Bronze	Rolled aluminum	Aluminum-cast, alloyed	Magnesium-cast, alloyed	Zinc-cast, alloyed	Titanium alloy	Thermo-setting plastics	Thermo-plastics	
C -0.25%	C0.25% -0.45%	C 0.45%-	SCM	25-45 HRC	45-55 HRC	50-60 HRC	SUS	SKD	SC	FC	FCD	Cu	Bs	BsC	PB	Al	AC ADC	MC	ZDC	Ti	Ni	-	-
○	◎	◎	○				○	○	○		○	○	○	○	○	○	○	○	○	○	○	○	

HSS Tap

SP type (Spiral Tap)



(mm)

Flutes	Designation		Thread size	L (Overall length)	I (Thread length)	d (Shank diameter)	K (Square width)	KI (Square length)	Limits
	2.5P								
	M3x0.5-SP25	M3X0.5	46	11	4	3.2	6		KH2
	M4x0.7-SP25	M4X0.7	52	13	5	4	7		
	M5x0.8-SP25	M5X0.8	60	16	5.5	4.5	7		
	M6x1.0-SP25	M6X1.0	62	19	6	4.5	7		
	M8x1.25-SP25	M8X1.25	70	22	6.2	5	8		
	M10x1.25-SP25	M10X1.25	75	24	7	5.5	8		
	M10x1.5-SP25	M10X1.5	75	24	7	5.5	8		
	M12x1.0-SP25	M12X1.0	82	29	8.5	6.5	9		
	M12x1.25-SP25	M12X1.25	82	29	8.5	6.5	9		
	M12x1.5-SP25	M12X1.5	82	29	8.5	6.5	9		
	M12x1.75-SP25	M12X1.75	82	29	8.5	6.5	9		
	M14x1.5-SP25	M14X1.5	88	30	10.5	8	11		
	M14x2.0-SP25	M14X2.0	88	30	10.5	8	11		
	M16x1.5-SP25	M16X1.5	95	32	12.5	10	13		KH3
	M16x2.0-SP25	M16X2.0	95	32	12.5	10	13		
	M18x1.5-SP25	M18X1.5	100	37	14	11	14		
	M18x2.5-SP25	M18X2.5	100	37	14	11	14		
	M20x1.5-SP25	M20X1.5	105	37	15	12	15		KH3
	M20x2.5-SP25	M20X2.5	105	37	15	12	15		

※ Built-up edges are prevented due to the reduced coefficient of friction by using porous cutting fluid of Fe304.


※ It is ideal for tapping SUS, cast steel, carbon steel for machine structure, etc.

Applicable Workpiece Range

Carbon steel			Alloy steel	Quenched and tempered steel			Stainless steel	Tool steel	Cast steel	Cast iron	Ductile cast iron	Copper	Brass	Brass-cast	Bronze	Rolled aluminum	Aluminum-cast, alloyed	Magnesium-cast, alloyed	Zinc-cast, alloyed	Titanium alloy	Thermo-setting plastics	Thermo-plastics	
C -0.25%	C0.25% -0.45%	C 0.45%-	SCM	25-45 HRC	45-55 HRC	50-60 HRC	SUS	SKD	SC	FC	FCD	Cu	Bs	BsC	PB	Al	AC ADC	MC	ZDC	Ti	Ni	-	-
◎	◎	◎	◎	◎	◎	◎	○	○	○	○	○												

HSS Tap

RT type (Roll Tap)



HSSE	Uncoated	Grade HN30T
------	----------	-------------

(mm)

Flutes	Designation		Thread size	L (Overall length)	I (Thread length)	d (Shank diameter)	K (Square width)	KI (Square length)	Limits
	2P	4P							
1	M3X0.5-RT20(S)	M3X0.5-RT40(S)	M3X0.5	46	11	4.0	3.2	6	KH5
4	M3X0.5-RT20(M)	M3X0.5-RT40(M)							
1	M4X0.7-RT20(S)	M4X0.7-RT40(S)	M4X0.7	52	13	5.0	4.0	7	KH6
4	M4X0.7-RT20(M)	M4X0.7-RT40(M)							
1	M5X0.8-RT20(S)	M5X0.8-RT40(S)	M5X0.8	60	16	5.5	4.5	7	KH6
4	M5X0.8-RT20(M)	M5X0.8-RT40(M)							
1	M6X1.0-RT20(S)	M6X1.0-RT40(S)	M6X1.0	62	19	6.0	4.5	7	KH6
4	M6X1.0-RT20(M)	M6X1.0-RT40(M)							
1	M8X1.25-RT20(S)	M8X1.25-RT40(S)	M8X1.25	70	22	6.2	5.0	8	KH7
4	M8X1.25-RT20(M)	M8X1.25-RT40(M)							
1	M10X1.25-RT20(S)	M10X1.25-RT40(S)	M10X1.25	75	24	7.0	5.5	8	KH7
4	M10X1.25-RT20(M)	M10X1.25-RT40(M)							
1	M10X1.5-RT20(S)	M10X1.5-RT40(S)	M10X1.5	75	24	7.0	5.5	8	KH7
4	M10X1.5-RT20(M)	M10X1.5-RT40(M)							
1	M12X1.0-RT20(S)	M12X1.0-RT40(S)	M12X1.0	82	29	8.5	6.5	9	KH7
4	M12X1.0-RT20(M)	M12X1.0-RT40(M)							
1	M12X1.25-RT20(S)	M12X1.25-RT40(S)	M12X1.25	82	29	8.5	6.5	9	KH8
4	M12X1.25-RT20(M)	M12X1.25-RT40(M)							
1	M12X1.5-RT20(S)	M12X1.5-RT40(S)	M12X1.5	82	29	8.5	6.5	9	KH8
4	M12X1.5-RT20(M)	M12X1.5-RT40(M)							
1	M12X1.75-RT20(S)	M12X1.75-RT40(S)	M12X1.75	82	29	8.5	6.5	9	KH8
4	M12X1.75-RT20(M)	M12X1.75-RT40(M)							


※ It is ideal for tapping non ferrous alloys such as aluminum, zinc, copper, etc.

Applicable Workpiece Range

Carbon steel			Alloy steel	Quenched and tempered steel			Stainless steel	Tool steel	Cast steel	Cast iron	Ductile cast iron	Copper	Brass	Brass-cast	Bronze	Rolled aluminum	Aluminum-cast, alloyed	Magnesium-cast, alloyed	Zinc-cast, alloyed	Titanium alloy		Thermo-setting plastics	Thermo-plastics
C -0.25%	0.25% -0.45%	C 0.45%	SCM	25-45 HRC	45-55 HRC	50-60 HRC	SUS	SKD	SC	FC	FCD	Cu	Bs	BsC	PB	Al	AC ADC	MC	ZDC	Ti	Ni	-	-
												○	○	○	○	○	○	○	○	○	○	○	○

HSS Tap

RT type (Roll Tap)



HSSE	TiN	Grade HC20T
------	-----	-------------

(mm)

Flutes	Designation		Thread size	L (Overall length)	I (Thread length)	d (Shank diameter)	K (Square width)	KI (Square length)	Limits
	2P	4P							
1	M3X0.5-RT20(S)	M3X0.5-RT40(S)	M3X0.5	46	11	4.0	3.2	6	KH5
4	M3X0.5-RT20(M)	M3X0.5-RT40(M)							
1	M4X0.7-RT20(S)	M4X0.7-RT40(S)	M4X0.7	52	13	5.0	4.0	7	KH6
4	M4X0.7-RT20(M)	M4X0.7-RT40(M)							
1	M5X0.8-RT20(S)	M5X0.8-RT40(S)	M5X0.8	60	16	5.5	4.5	7	KH6
4	M5X0.8-RT20(M)	M5X0.8-RT40(M)							
1	M6X1.0-RT20(S)	M6X1.0-RT40(S)	M6X1.0	62	19	6.0	4.5	7	KH6
4	M6X1.0-RT20(M)	M6X1.0-RT40(M)							
1	M8X1.25-RT20(S)	M8X1.25-RT40(S)	M8X1.25	70	22	6.2	5.0	8	KH6
4	M8X1.25-RT20(M)	M8X1.25-RT40(M)							
1	M10X1.25-RT20(S)	M10X1.25-RT40(S)	M10X1.25	75	24	7.0	5.5	8	KH6
4	M10X1.25-RT20(M)	M10X1.25-RT40(M)							
1	M10X1.5-RT20(S)	M10X1.5-RT40(S)	M10X1.5	75	24	7.0	5.5	8	KH7
4	M10X1.5-RT20(M)	M10X1.5-RT40(M)							
1	M12X1.0-RT20(S)	M12X1.0-RT40(S)	M12X1.0	82	29	8.5	6.5	9	KH7
4	M12X1.0-RT20(M)	M12X1.0-RT40(M)							
1	M12X1.25-RT20(S)	M12X1.25-RT40(S)	M12X1.25	82	29	8.5	6.5	9	KH7
4	M12X1.25-RT20(M)	M12X1.25-RT40(M)							
1	M12X1.5-RT20(S)	M12X1.5-RT40(S)	M12X1.5	82	29	8.5	6.5	9	KH7
4	M12X1.5-RT20(M)	M12X1.5-RT40(M)							
1	M12X1.75-RT20(S)	M12X1.75-RT40(S)	M12X1.75	82	29	8.5	6.5	9	KH8
4	M12X1.75-RT20(M)	M12X1.75-RT40(M)							

※ It is for general use for both steels and non ferrous metal.


※ Wear resistance was much improved by the use of TiCN coating for high efficiency tapping operations.

Applicable Workpiece Range

Carbon steel			Alloy steel	Quenched and tempered steel			Stainless steel	Tool steel	Cast steel	Cast iron	Ductile cast iron	Copper	Brass	Brass-cast	Bronze	Rolled aluminum	Aluminum-cast, alloyed	Magnesium-cast, alloyed	Zinc-cast, alloyed	Titanium alloy	Thermo-plastics	Thermo-plastics	
C -0.25%	C -0.45%	C 0.45%	SCM	25-45 HRC	45-55 HRC	50-60 HRC	SUS	SKD	SC	FC	FCD	Cu	Bs	BsC	PB	Al	AC ADC	MC	ZDC	Ti	Ni	-	-
◎	◎	◎	◎	◎	◎	◎	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	

HSS Tap

RT type (Roll Tap)



HSSE

TiCN

Grade
HC10T

(mm)

Flutes	Designation		Thread size	L (Overall length)	I (Thread length)	d (Shank diameter)	K (Square width)	Ki (Square length)	Limits
	2P	4P							
1	M3X0.5-RT20(S)	M3X0.5-RT40(S)	M3X0.5	46	11	4.0	3.2	6	KH5
4	M3X0.5-RT20(M)	M3X0.5-RT40(M)							
1	M4X0.7-RT20(S)	M4X0.7-RT40(S)	M4X0.7	52	13	5.0	4.0	7	KH6
4	M4X0.7-RT20(M)	M4X0.7-RT40(M)							
1	M5X0.8-RT20(S)	M5X0.8-RT40(S)	M5X0.8	60	16	5.5	4.5	7	KH6
4	M5X0.8-RT20(M)	M5X0.8-RT40(M)							
1	M6X1.0-RT20(S)	M6X1.0-RT40(S)	M6X1.0	62	19	6.0	4.5	7	KH6
4	M6X1.0-RT20(M)	M6X1.0-RT40(M)							
1	M8X1.25-RT20(S)	M8X1.25-RT40(S)	M8X1.25	70	22	6.2	5.0	8	KH7
4	M8X1.25-RT20(M)	M8X1.25-RT40(M)							
1	M10X1.25-RT20(S)	M10X1.25-RT40(S)	M10X1.25	75	24	7.0	5.5	8	KH7
4	M10X1.25-RT20(M)	M10X1.25-RT40(M)							
1	M10X1.5-RT20(S)	M10X1.5-RT40(S)	M10X1.5	75	24	7.0	5.5	8	KH7
4	M10X1.5-RT20(M)	M10X1.5-RT40(M)							
1	M12X1.0-RT20(S)	M12X1.0-RT40(S)	M12X1.0	82	29	8.5	6.5	9	KH8
4	M12X1.0-RT20(M)	M12X1.0-RT40(M)							
1	M12X1.25-RT20(S)	M12X1.25-RT40(S)	M12X1.25	82	29	8.5	6.5	9	KH8
4	M12X1.25-RT20(M)	M12X1.25-RT40(M)							
1	M12X1.5-RT20(S)	M12X1.5-RT40(S)	M12X1.5	82	29	8.5	6.5	9	KH8
4	M12X1.5-RT20(M)	M12X1.5-RT40(M)							
1	M12X1.75-RT20(S)	M12X1.75-RT40(S)	M12X1.75	82	29	8.5	6.5	9	KH8
4	M12X1.75-RT20(M)	M12X1.75-RT40(M)							

※ It is for general use for both steels and non ferrous metal.


※ Wear resistance was much improved by the use of TiCN coating for high efficiency tapping operations.

Applicable Workpiece Range

Carbon steel			Alloy steel	Quenched and tempered steel			Stainless steel	Tool steel	Cast steel	Cast iron	Ductile cast iron	Copper	Brass	Brass-cast	Bronze	Rolled aluminum	Aluminum-cast, alloyed	Magnesium-cast, alloyed	Zinc-cast, alloyed	Titanium alloy	Thermo-plastics	Thermo-plastics	
C -0.25%	C -0.45%	C 0.45%	SCM	25-45 HRC	45-55 HRC	50-60 HRC	SUS	SKD	SC	FC	FCD	Cu	Bs	BsC	PB	Al	AC ADC	MC	ZDC	Ti	Ni	-	-
◎	◎	○	○			◎						◎	◎	◎		◎	◎		◎				

HSS Tap

SR type (Spiral Roll Tap)



HSSE	Uncoated	Grade HN30T
------	----------	-------------

(mm)

Designation		Thread size	L (Overall length)	I (Thread length)	d (Shank diameter)	K (Square width)	KI (Square length)	Limits
2P	4P							
M3X0.5-SR20	M3X0.5-SR40	M3X0.5	46	18	4.0	3.2	6	KH6
M3.5X0.6-SR20	M3.5X0.6-SR40	M3.5X0.6	46	18	4.0	3.2	6	
M4X0.7-SR20	M4X0.7-SR40	M4X0.7	52	20	5.0	4.0	7	KH7
M5X0.8-SR20	M5X0.8-SR40	M5X0.8	60	22	5.5	4.5	7	
M6X1.0-SR20	M6X1.0-SR40	M6X1.0	62	24	6.0	4.5	7	


※ It is for general use for tapping aluminum, magnesium and zinc as well as non ferrous metal.

Applicable Workpiece Range

Carbon steel			Alloy steel	Quenched and tempered steel			Stainless steel	Tool steel	Cast steel	Cast iron	Ductile cast iron	Copper	Brass	Brass-cast	Bronze	Rolled aluminum	Aluminum-cast, alloyed	Magnesium-cast, alloyed	Zinc-cast, alloyed	Titanium alloy	Thermo-setting plastics	Thermoplastics	
C -0.25%	C0.25% -0.45%	C 0.45%-	SCM	25-45 HRC	45-55 HRC	50-60 HRC	SUS	SKD	SC	FC	FCD	Cu	Bs	BsC	PB	AI	AC ADC	MC	ZDC	Ti	Ni	-	-
												O	O	O	O	O	O	O	O				

HSS Tap

SR type (Spiral Roll Tap)



HSSE

TiN

Grade
HC20T

(mm)

Designation		Thread size	L (Overall length)	I (Thread length)	d (Shank diameter)	K (Square width)	KI (Square length)	Limits
2P	4P							
M3X0.5-SR20	M3X0.5-SR40	M3X0.5	46	18	4.0	3.2	6	KH6
M3.5X0.6-SR20	M3.5X0.6-SR40	M3.5X0.6	46	18	4.0	3.2	4	
M4X0.7-SR20	M4X0.7-SR40	M4X0.7	52	20	5.0	4.0	7	
M5X0.8-SR20	M5X0.8-SR40	M5X0.8	60	22	5.5	4.5	7	
M6X1.0-SR20	M6X1.0-SR40	M6X1.0	62	24	6.0	4.5	7	

※ It is ideal for tapping steel, non ferrous metal and stainless steel.


※ Wear resistance was much improved by the use of TiCN coating for high efficiency tapping operations.

Applicable Workpiece Range

Carbon steel			Alloy steel	Quenched and tempered steel			Stainless steel	Tool steel	Cast steel	Cast iron	Ductile cast iron	Copper	Brass	Brass-cast	Bronze	Rolled aluminum	Aluminum-cast, alloyed	Magnesium-cast, alloyed	Zinc-cast, alloyed	Titanium alloy	Thermo-setting plastics	Thermoplastics	
C -0.25%	C0.25% -0.45%	C 0.45%-	SCM	25-45 HRC	45-55 HRC	50-60 HRC	SUS	SKD	SC	FC	FCD	Cu	Bs	BsC	PB	Al	AC ADC	MC	ZDC	Ti	Ni	-	-
○	○	○	○				◎	○	○		○	○	○	○									

HSS Tap

SR type (Spiral Roll Tap)



HSSE

TiCN

Grade
HC10T

(mm)

Designation		Thread size	L (Overall length)	I (Thread length)	d (Shank diameter)	K (Square width)	KI (Square length)	Limits
2P	4P							
M3X0.5-SR20	M3X0.5-SR40	M3X0.5	46	18	4.0	3.2	6	KH6
M3.5X0.6-SR20	M3.5X0.6-SR40	M3.5X0.6	46	18	4.0	3.2	6	
M4X0.7-SR20	M4X0.7-SR40	M4X0.7	52	20	5.0	4.0	7	
M5X0.8-SR20	M5X0.8-SR40	M5X0.8	60	22	5.5	4.5	7	
M6X1.0-SR20	M6X1.0-SR40	M6X1.0	62	24	6.0	4.5	7	

※ It is ideal for tapping steel, non ferrous metal and stainless steel.

※ Wear resistance was much improved by the use of TiCN coating for high efficiency tapping operations.


Applicable Workpiece Range

Carbon steel			Alloy steel	Quenched and tempered steel			Stainless steel	Tool steel	Cast steel	Cast iron	Ductile cast iron	Copper	Brass	Brass-cast	Bronze	Rolled aluminum	Aluminum-cast, alloyed	Magnesium-cast, alloyed	Zinc-cast, alloyed	Titanium alloy	Thermo-setting plastics	Thermoplastics	
C -0.25%	C0.25% -0.45%	C 0.45%-	SCM	25-45 HRC	45-55 HRC	50-60 HRC	SUS	SKD	SC	FC	FCD	Cu	Bs	BsC	PB	AI	AC ADC	MC	ZDC	Ti	Ni	-	-
◎	◎	○	○			◎					◎	◎	◎		◎	◎		◎					

Tapping Chuck - DST


Specially designed structure for absorbing thrust load and preventing damage on the tap. Through coolant system available.
Applicable range: M1-M22

Code System



Precise Machining


Exclusive collet for tapping: Use TER collet at tapping work. Use ER11 collet for DST7.



Comparison of Thread Figures


Type	Collet chuck	DST7	Competitor
Intro part after one time use			
End part after one time use			

When tapping under the same conditions, threads of a general collet chuck seem to be damaged.



Tapping Chuck


BT-DST



Designation		Tapping range	ØD	ØD ₁	L	S	Collet	F-	F+	(mm)
BT30 -	DST3-70	M1-M3	26	19	70	6	ER11	0.5	0.5	
	DST10-95	M3-M10	40.4	28	95	11	TER16	0.5	0.5	
BT40 -	DST10-100	M3-M10	40.4	28	100	11	TER16	0.5	0.5	
	DST22-110	M6-M22	60	49.5	110	18	TER32	0.7	0.7	
BT50 -	DST10-110	M3-M10	60	49.5	110	11	TER16	0.5	0.5	
	DST22-130	M6-M22	60	49.5	125	18	TER32	0.7	0.7	

※ Through coolant system is optional.

HSK-DST



Designation		Tapping range	ØD	ØD ₁	L	S	Collet	F-	F+	(mm)
HSK63A -	DST10-100	M3~M10	40.4	28	100	11	TER16	0.5	0.5	
	DST10-130	M6~M22	60	49.5	130	18	TER32	0.7	0.7	

※ Through coolant system is optional.

Tapping Chuck - DTN

Easy and fast tool change. Minimizes tap breakage by the use of a malleable and shrinkable adaptor.


Applicable range: M3 - M38

Code System


BT40	-	DTN	-	22	-	130
Spindle		Tapping holder		Max. chucking dia.		Length

Easy Exchange of TCA (Tap adaptor)

- Convenient one-touch exchange type for high precision and longer tool life.
- Fast tool change of various sizes enables a wide range of applications.
- Length is shrinkable by the axial floating way.




How to clamp TCA and a Tap holder



Tapping Chuck

BT-DTN




(mm)

Designation		Tapping range	L	L ₁	ØC	ØC ₁	F-	F+	$\frac{\text{kg}}{\text{kg}}$	Adaptor
BT30 -	DTN12-85	M3~M12	85	60	32	39	4	10	0.7	TCA1-M
BT40 -	DTN12-90	M3~M12	90	65	32	39	4	10	1.2	TCA1-M
	DTN12-120	M3~M12	120	95	32	39	4	10	1.4	TCA1-M
	DTN22-130	M8~M22	130	96	50	56	12.5	12.5	1.7	TCA2-M
	DTN22-160	M8~M22	160	126	50	56	12.5	12.5	2.1	TCA2-M
BT50 -	DTN12-100	M3~M12	100	75	32	39	4	10	3.7	TCA1-M
	DTN12-130	M3~M12	130	105	32	39	4	10	3.9	TCA1-M
	DTN22-140	M8~M22	140	104	50	56	12.5	12.5	4.2	TCA2-M
	DTN22-170	M8~M22	170	134	50	56	12.5	12.5	4.7	TCA2-M
	DTN38-185	M16~M38	185	140	72	81	20	20	5.7	TCA3-M
	DTN38-215	M16~M38	215	170	72	81	20	20	6.6	TCA3-M

※ Through coolant system is optional.

S-DTN




(mm)

Designation		Tapping range	L	L ₁	ØC	ØC ₁	F-	F+	F-	F+	Adaptor
S32 -	DTN12-90	M3-M12	32	170	90	65	32	39	4	10	TCA1
	DTN22-130	M8-M24	32	210	130	96	50	56	12.5	12.5	TCA2

※ Through coolant system is optional.

Tapping Chuck

TCA (Tap adaptor)



(mm)




Designation	ØD	ØC	L	L ₁	Δ_{kg}	
TCA1 -	M3	4	3.2	24	22	0.2
	M4	5	4	24	22	0.2
	M5	5.5	4.5	24	22	0.2
	M6, 1/4U	6	4.5	24	22	0.2
	M8	6.2	5	25	22	0.2
	M10, 3/8U	7	5.5	25	22	0.2
	M11	8	6	39	22	0.2
	M12	8.5	6.5	26	22	0.2
TCA2 -	M8	6.2	5	38	28	0.6
TCS2 -	M10	7	5.5	38	28	0.6
TCA2 -	M12	8.5	6.5	39	28	0.6
	M14, 3/4U	10.5	8	41	28	0.6
	P1/4	11	9	31	28	0.6
TCS2 -	M16	12.5	10	43	28	0.6
TCA2 -	M18, P3/8	14	11	44	28	0.6
	M20	15	12	45	28	0.6
	M22	17	13	46	28	0.6
	P1/2	18	14	36	28	0.6
	M24	19	15	46	28	1.8
TCA3 -	M16	12.5	10	35	37	1.8
	M18	14	11	37	37	1.8
	M20	15	12	37	37	1.8
	M22	17	13	38	37	1.8
	M24	19	15	44	37	1.8
	M27, 1U	20	15	62	37	1.8
	M30, P3/4	23	17	62	37	1.8
	M33	25	19	66	37	1.8
	M36, M38	28	21	68	37	1.8

※ DIN standard products are custom-made.

※ Through coolant system is not available.

TAP series

TER (Tap collet)




(mm)


Designation		Applicable Tap	$\varnothing D$	W	$\varnothing C$	$\varnothing C_1$	L	L_1	H
TER16 -	4x3.2	M3	4	3.2	16.74	10.1	27.5	6.3	18
	5x4	M4	5	4	16.74	10.1	27.5	6.3	18
	5.5x4.5	M5	5.5	4.5	16.74	10.1	27.5	6.3	18
	6x4.5	M6, U1/4	6	4.5	16.74	10.1	27.5	6.3	18
	6.2x5	M7, M8	6.2	5	16.74	10.1	27.5	6.3	18
	7x5.5	M9, M10, U3/8	7	5.5	16.74	10.1	27.5	6.3	18
TER20 -	5x4	M4	5	4	20.74	13.2	31.5	7.2	18
	5.5x4.5	M5	5.5	4.5	20.74	13.2	31.5	7.2	18
	6x4.5	M6, U1/4	6	4.5	20.74	13.2	31.5	7.2	18
	6.2x5	M7, M8	6.2	5	20.74	13.2	31.5	7.2	18
	7x5.5	M9, M10, U3/8	7	5.5	20.74	13.2	31.5	7.2	18
	8x6	M11, U7/16, P1/8	8	6	20.74	-	-	-	-
	8.5x6.5	M12	8.5	6.5	20.74	13.2	31.5	7.2	22
TER25 -	5x4	M4	5	4	25.74	17.6	34	7.5	18
	5.5x4.5	M5	5.5	4.5	25.74	17.6	34	7.5	18
	6x4.5	M6	6	4.5	25.74	17.6	34	7.5	18
	6.2x5	M7, M8	6.2	5	25.74	17.6	34	7.5	18
	7x5.5	M9, M10, U3/8	7	5.5	25.74	17.6	34	7.5	18
	8.5x6.5	M12	8.5	6.5	25.74	17.6	34	7.5	22
TER32 -	6x4.5	M6, U1/4	6	4.5	32.74	23.1	40	8.2	18
	6.2x5	M7, M8	6.2	5	32.74	23.1	40	8.2	18
	7x5.5	M9, M10, U3/8	7	5.5	32.74	23.1	40	8.2	18
	8x6	M11, U7/16, P1/8	8	6	32.74	23.1	40	8.2	22
	8.5x6.5	M12	8.5	6.5	32.74	23.1	40	8.2	22
	10.5x8	M14, U9/16	10.5	8	32.74	23.1	40	8.2	25
	12.5x10	M16	12.5	10	32.74	23.1	40	8.2	25
	14x11	M18, P3/8	14	11	32.74	23.1	40	8.2	25
	15x12	M20	15	12	32.74	23.1	40	8.2	25
	17x13	M22, U7/8	17	13	32.74	23.1	40	8.2	25
	11x9	P1/4	11	9	32.74	23.1	40	8.2	25
	12x9	U5/8	12	9	32.74	23.1	40	8.2	25
	9x7	U1/2	9	7	32.74	23.1	40	8.2	22

※ Machining with a waterproof tap is possible by using RTJW and RUT nuts. (only in right sizes)

Notes



0 5 25mm



Head Office

Holystar B/D, 1350, Nambusunhwon-ro, Geumcheon-gu, Seoul, 08536, Korea Web: www.korloy.com

Cheongju Factory

55, Sandan-ro, Heungdeok-gu, Cheongju-si, Chungcheongbuk-do, 28589, Korea

Jincheon Factory

54, Gwanghyewonsandan 2-gil, Gwanghyewon-myeon, Jincheon-gun, Chungcheongbuk-do, 27807, Korea

R & D Institute Cheongju

55, Sandan-ro, Heungdeok-gu, Cheongju-si, Chungcheongbuk-do, 28589, Korea

R & D Institute Seoul

Holystar B/D, 1350, Nambusunhwon-ro, Geumcheon-gu, Seoul, 08536, Korea



Gablonzer Straße 25-27, D-61440 Oberursel, Germany, Tel: +49-6171-27783-0, Fax: +49-6171-27783-59
E-Mail: info@korloyeurope.com, Web: www.korloyeurope.com



620 Maple Avenue, Torrance, CA 90503, USA



Ground Floor, Property No. 217, Udyog Vihar Phase 4, Gurgaon 122016, Haryana, India



Av. Aruana 280, conj.12, WLC, Alphaville, Barueri, CEP06460-010, SP, Brasil



No. 133 Le Loi street, Hoa Phu ward, Thu Dau Mot city, Binh Duong proviende, Vietnam



Ground Dongjing Road 56 District Free Trade Zone. Qingdao, China



Plot No. 415, Sector 8, IMT Manesar, Gurgaon 122051, Haryana, India

KTS - Korloy Tooling Solution



Get our FREE App

Just download, install and use.



20200701

TN71-EN-02